

# **OMEGA INDUSTRIES**

AN ISO 9001:2008 COMPANY

## MANUFACTURERS OF INDUSTRIAL OILS AND GREASES

PLOT NO. E-21, M.I.D.C. KUPWAD, Dist. - Sangli 416 436. (Maharashtra) Phone No.: 0233-2645101 / 2644201

E-mail: omega\_sangli@yahoo.com E-mail: omegaindustriese21@gmail.com

#### **ELITE QUICK 101**

(Integral water reducing Fast Curing & Hardening Concrete Compound)

PRODUCT INFORMATION: It is liquid integral water proofing and water reducing admixture. It gives high end strength and excellent plasticizing effect along with better water reducing quality, plasticizer for Slabs, columns, walls, foundations and pavements, electric cement poles, pcc pipes etc.

#### USES AND ADVANTAGES:

- Used for best quality concrete and ready-mix concrete.
- Compatible with all types of cement.
- Gives best surface finish.
- Keeps safe re-enforcement. Corrosion resistance for steel.
- Can be used in high temp. area.
- Retains long period slump flow.
- Best water reduction and tightness.
- Very good waterproofing and workability.
- Best ultimate compressive strength.

### MEETS: IS 9103 – 1999 and ASTM C494

MEETS: IS 9103 – 1999 and ASTM C494		Results
Sr.No.	Parameters	
01.	Appearance	Brown Liquid
	Form	Liquid
02.		12 Months
03.	Self life	1.170 Kg./Ltr@25°C
04.	Density	
05	PH	6
06.	Solubility	Soluble in Water
07.	Boiling Point	100°C
		Product Specific
08.	Odour	· Elevanorial de la companya della companya de la companya della c

Dosage: 1.5 % to 2% weight of cement.

Packaging: 20 Kgs. /50 Kgs. /250 Kg.

#### PRECAUTIONS:

- Stir well before use
- Do not add excessive water to avoid bleeding.
- Fresh concrete must be cured as per normal standards.
- Clean all equipments immediately after finishing job.
- Follow recent safety norms e.g. Toxicological, workmen safety and ecological.

Legal Notes: The user should test the product suitability before major work to select dose size etc. In practice the differences in material, sand, cement, substrates and actual site atmospheric condition like, temperature, rain and cold etc. are variable and uncontrollable and are such that no warranty in respect of fitness and merchantability for particular purpose. All technical information above is on the basis of our Lab. Trials. Actual data may vary due to site conditions beyond our control.