PRODUCT DATA SHEET

01. **PRODUCT NAME**: FORMOL - 500 (Water Emulsion Mould Releasing Oil)

02. **COMPANY NAME & ADDRESS:** M/s. OMEGA INDUSTRIES,

   PLOT NO. E -21, M.I.D.C. KUPWAD, DIST- SANGLI- 416 436 (MAHARASHTRA) (INDIA)

03. **USE:** FORMOL-500 can be used to Steel Moulds so that all types of Pre-Cast Products manufacturers like Railway Concrete Sleeper, PCC Poles, Building Construction, Bridge Construction & any Pre-Cast products etc. can be released smoothly without sticking. It gives excellent surface finish.

04. **CHEMICAL HAZARD:** FORMOL -500 does not contain any Hazardous Chemicals. It is safe for Human Hands.

05. **FLAMMABILITY:** Not Flammable

06. **FIRE HAZARD:** NIL.

07. **ATTENTION:** Roll well before use.

08. **MAIN BENEFITS :**

   • Smooth Releasing of Concrete products.

   • Good oiliness.

   • Resistant to wash off by water.

   • Gives excellent surface finishing.

   • Keeps Metal Moulds Shining & Prevents Rusting.

   • Contains no waxes, silicones.

09. **TESTS :**

-	Colour	-	Pink
-	Appearance	-	Liquid
-	Specific Gravity	-	0.950
-	Viscosity B4 Cup at RT 29^0C	-	80 to 85 sec.
-	Drying Time	-	Does not dry.
-	Water Repellent Test	-	Excellent Water Repellent.
-	Acidity & Alkalinity	-	Nil
-	Coverage	-	30 to 35 Sq.Mtr. /Ltr.
-	Solids	-	Not More than 2%
-	Self-Life	-	120 Days